

OCEANIC COLLECTION TECHNICAL SPECIFICATIONS	
Luxury Vinyl Tile	NCPC-T LVT Floor
Madera Wood	182 x 1218mm (7 x 48") Micro bevelled as standard Special finishes and straight edges available
Terra	304 x 609mm (12 x 24") Micro bevelled as standard Special finishes and straight edges available
Gauge	2.5mm
Wear Layer	0.5mm
Total weight	4.49kg/m ²
UV Coating volume	8-10g/m ²
Application Area	EN685 21-34 and 43
Staining Resistance	ISO 26987 Pass
Castor Load	ISO 4918 25000 round pass
Squareness & Straightness	ISO 24341 Pass
Dimensional Stability	ISO 23999 Pass
Scratch Resistance	≥2500g
Residual Indentation	≥0.10mm ISO 24343-1
Slip Resistance	R10 DIN 51130
Noise Dampening	3db
Light Fastness	≥6 ISO 105-B02
Underfloor heating	Yes to max 27°
Fire Rating	IMO Certified
Warranty	10 year limited
technical@ovationflooring.com	

Design Strips are available in any tile from the collection and in a myriad of plain colours in different sizes

Special design features cut to your specification



marine@ovationflooring.com

www.ovationflooring.com