

LUVANTO FR MARINE TECHNICAL SPECIFICATIONS	
Luxury Vinyl Tile	
Wood	152 x 914mm (6 x 36") Standard 184 x 1219 (7 x 48") 76 x 305mm (3 x 12") Herringbone Bevelled Edge on all four sides
Stone	305 x 610mm (12 x 24") Standard 457 x 457mm (18 x 18") Bevelled Edge
Metal	457 x 457mm (18 x 18") Square Edge
Sparkle	457 x 457mm (18 x 18") Square Edge
Design Insert Strips	914 x 5mm (36" x 5mm) in 14 colours
Gauge	2.5mm
Wear Layer	EN429 0.5mm
Application Area	EN685 23, 32
Total Weight	EN430 4600g/m ²
Squareness and Straightness	EN427 ≤0.12mm/≤0.15mm
Surface Treatment	PU
Abrasion Wear Resistance	EN660-2 Group P
Friction / Slip Resistance	DIN 51130 R10
Chemical & Stain Resistance	EN423 Approved
Residual Indentation	EN433 ≤0.1mm
Castor Load	EN425 Approved
Colour Fastness to Light	ISO 105 B02 ≤6
Curling	EN434 ≤2mm
Dimensional Stability / Shrinkage	EN434 Approved ≤0.25%
Flexibility	EN435 Approved
Sound Reduction	DIN 52210 – 4db
Underfloor heating	Yes to max 27°
Fire Rating	IMO Certified
technical@ovationflooring.com	

Special design features cut to your specification



marine@ovationflooring.com

www.ovationflooring.com